## NSN 5999-01-169-5092



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-169-5092 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.750 inches **Body Width:** 0.270 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -0.0/+80.0 degrees celsius **Mounting Facility Quantity:** 14 **Voltage Rating:** 50.000 volts **Material And Location:** Plastic, epoxy case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth: 18000.0 kilohertz **Body Depth:** 0.230 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 12.000

**Signal Delay Method:** 

Lumped constant

**Delay Time Variation Method:** 

**Tapped** 

## NSN 5999-01-169-5092

Delay Line - Page 2 of 2



Section Delay Time:
100.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:

10.000 nanoseconds single section all segments

**Delay Time Variation Per Deg Celsius:** 

Not rated

Pulse Rise Time Rating:

20.0 nanoseconds

**Terminal Type And Quantity:** 

14 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100