NSN 5999-01-174-3182



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-174-3182 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.780 inches **Body Width:** 0.460 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Shortest Horizontal Distance Between Mounting Centers:** 0.200 inches **Intermediate Horizontal Distance Between Mounting Centers:** Any acceptable **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Mounting Facility Quantity:** 4 **Voltage Rating:** Not rated Input Impedance Rating: 250.000 ohms **Output Impedance Rating:** 250.000 ohms Frequency Bandwidth: 60000.0 kilohertz **Body Depth:** 0.250 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position off-set **Attenuation In Decibels:** Not rated

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

NSN 5999-01-174-3182

Delay Line - Page 2 of 2



30.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

6.0 nanoseconds

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100