NSN 5999-01-176-1227



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-176-1227 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.810 inches **Body Width:** 0.410 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 4 **Voltage Rating:** 0.800 volts **Material And Location:** Any acceptable **Surface Treatment And Location:** Any acceptable Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: 75.0 hertz **Body Depth:** 0.260 inches

Mounting Facility: Unthreaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:**

Tapped

NSN 5999-01-176-1227

Delay Line - Page 2 of 2



Section	Delay	Time:
Section	Delay	HIIIIE.

100.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

2.0 nanoseconds

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100