## NSN 5999-01-176-1758



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-176-1758 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.810 inches **Body Width:** 0.410 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 4 **Voltage Rating:** 0.800 volts **Material And Location:** Any acceptable case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.260 inches **Mounting Facility:** Unthreaded hole **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** 

Lumped constant

Delay Time Variation Method:

Tapped

## NSN 5999-01-176-1758

Delay Line - Page 2 of 2



Section Delay Time:
50.000 nanoseconds single section
<b>Delay Time Variation Per Deg Celsius:</b>
Not rated
Pulse Rise Time Rating:
4.0 nanoseconds
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A32100