

View Online at <https://aerobasegroup.com/nsn/5999-01-176-9185>

**Body Style:**

Rectangular

**Frequency Rating:**

0.480 megahertz

**Body Length:**

0.725 inches

**Body Width:**

0.290 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.325 inches

**Longest Vertical Distance Between Mounting Centers:**

0.180 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Mounting Facility Quantity:**

4

**Voltage Rating:**

2.250 volts

**Material And Location:**

Plastic, mil-m-14, type sgd-f case

**Surface Treatment And Location:**

Any acceptable case

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Body Depth:**

0.225 inches

**Mounting Facility:**

Terminal

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

0.100

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

50.000 nanoseconds single section

**Delay Time Variation Per Deg Celsius:**

1.000 nanoseconds

**Pulse Rise Time Rating:**

9.5 nanoseconds

**Terminal Type And Quantity:**

4 wire leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100