

View Online at <https://aerobasegroup.com/nsn/5999-01-176-9185>

Body Style:

Rectangular

Frequency Rating:

0.480 megahertz

Body Length:

0.725 inches

Body Width:

0.290 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.325 inches

Longest Vertical Distance Between Mounting Centers:

0.180 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

4

Voltage Rating:

2.250 volts

Material And Location:

Plastic, mil-m-14, type sgd-f case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

0.225 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

0.100

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

50.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

1.000 nanoseconds

Pulse Rise Time Rating:

9.5 nanoseconds

Terminal Type And Quantity:

4 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100