NSN 5999-01-179-4700

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-179-4700

Body Style:
Rectangular
Body Length:
0.790 inches
Body Width:
Between 0.240 inches and 0.280 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
14
Voltage Rating:
50.000 volts
Surface Treatment And Location:
Gold, mil-g-45204, type 2, class 2 terminal or tin plate, mil-t-10727, type 1 or 2 terminal or copper terminal
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Body Depth:
0.200 inches
Mounting Facility:
Terminal
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
10.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
1.000 nanoseconds single section all segments
Pulse Rise Time Rating:
2.0 nanoseconds
Terminal Type And Quantity:
14 tab solder lug
Precious Material And Location:

Terminal surfaces gold

NSN 5999-01-179-4700

Delay Line - Page 2 of 2



_			
u	racialie	Material	•

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100