## NSN 5999-01-180-3438

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-180-3438

Body Style: Rectangular Body Length:

0.760 inches

**Body Width:** 

0.290 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.600 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.300 inches and 0.350 inches

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Mounting Facility Quantity:** 

14

Material And Location:

Plastic, epoxy case

Input Impedance Rating:

200.000 ohms

**Output Impedance Rating:** 

200.000 ohms

Body Depth:

0.225 inches

**Mounting Facility:** 

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

0.500

Signal Delay Method:

Lumped constant

**Delay Time Variation Method:** 

Tapped

Section Delay Time:

10.000 nanoseconds single section

#### Segment Quantity Per Section:

10 single section

Segment Delay Time:

1.000 nanoseconds single section all segments

Pulse Rise Time Rating:

2.5 nanoseconds

# NSN 5999-01-180-3438

Delay Line - Page 2 of 2



### Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

Fiig:

A32100