## NSN 5999-01-181-6040

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-181-6040 **Body Style:** Rectangular **Body Length:** 0.760 inches **Body Width:** 0.290 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** Between 0.300 inches and 0.350 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 14 **Material And Location:** Plastic, epoxy case Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms **Body Depth:** 0.225 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 0.500 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 56.000 nanoseconds single section **Segment Quantity Per Section:** 7 single section **Segment Delay Time:** 7.000 nanoseconds single section all segments

Pulse Rise Time Rating: 10.0 nanoseconds

## NSN 5999-01-181-6040

Delay Line - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

14 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100