

View Online at <https://aerobasegroup.com/nsn/5999-01-184-6299>

Overall Length:

0.650 inches

Pin Diameter:

0.017 inches

Overall Diameter:

0.095 inches

Cable Entrance Diameter:

0.083 inches

Current Rating In Amps:

1.0

Mounting Method:

Spring tension

Material:

Plastic contact insulation

Material Specification:

L-p-394, fscm 80249 mfr ref single material response contact insulation

Precious Material And Location:

Body and contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Gold contact and copper contact

Surface Treatment Specification:

Mil-g-45024, type 2 military specification 1st treatment response contact and mil-c-14550 military specification 2nd treatment response contact

Style Designator:

Pin center contact

Test Data Document:

80249-351767 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 solder well end opposite contact

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A222a0

Mil-std (military Standard):

Mil-c-50 spec.