## NSN 5999-01-187-6379



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-187-6379 **Body Style:** Rectangular **Body Length:** 0.750 inches **Body Width:** 0.300 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** Between 0.310 inches and 0.350 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 14 **Voltage Rating:** 5.000 volts **Material And Location:** Plastic, epoxy case Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms **Body Depth:** 0.225 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 0.500 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 

15 single section

150.000 nanoseconds single section

Segment Quantity Per Section:

## NSN 5999-01-187-6379

Delay Line - Page 2 of 2



Segment Delay Time:	Se	qm	ent	Del	lav	Tin	ne:
---------------------	----	----	-----	-----	-----	-----	-----

10.000 nanoseconds single section all segments

Pulse Rise Time Rating:

19.0 nanoseconds

**Terminal Type And Quantity:** 

14 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100