## NSN 5999-01-188-7161

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-188-7161 **Body Style:** Rectangular **Body Length:** 0.750 inches **Body Width:** 0.300 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+130.0 degrees celsius **Mounting Facility Quantity:** 14 **Voltage Rating:** 5.000 volts **Material And Location:** Plastic, epoxy body Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms **Body Depth:** 0.320 inches **Mounting Facility:** Pin **Attenuation In Decibels:** 5.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 20.000 nanoseconds single section **Delay Time Variation Per Deg Celsius:** 2.000 nanoseconds **Pulse Rise Time Rating:** 5.5 nanoseconds **Terminal Type And Quantity:** 14 pin **Test Data Document:** 

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

## NSN 5999-01-188-7161

Delay Line - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100