NSN 5999-01-196-1426

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-196-1426

Thread C	lass:
----------	-------

2b

Thread Pitch Diameters:

+0.0874/+0.0902 inches

Body Style:

Rectangular

Body Length:

2.000 inches

Body Width:

1.000 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.500 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Operating Tempurature Range:

+0.0/+90.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Quantity:

2

Material And Location:

Plastic case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Frequency Bandwidth:

1000.0 kilohertz

Body Depth:

0.500 inches

Mounting Facility:

Threaded hole

Mounting Provision Arrangement Style:

2 position diagonal

Attenuation In Decibels:

3.000

Signal Delay Method:

Lumped constant

NSN 5999-01-196-1426

Delay Line - Page 2 of 2



Delay Time Variation Method:

Variable

Section Delay Time:

4.200 microseconds single section

Terminal Type And Quantity:

3 pin

Thread Size And Series/type Designator:

0.112-40 unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100