NSN 5999-01-199-2866



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-199-2866 **Body Style:** Rectangular **Body Length:** 0.900 inches **Body Width:** 0.280 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.700 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Voltage Rating: 50.000 volts **Material And Location:** Iron alloy case **Surface Treatment And Location:** Tin plate case Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms **Body Depth:** 0.280 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 30.000 nanoseconds single section **Delay Time Variation Per Deg Celsius:**

30.000 nanoseconds single sect

Delay Time Variation Per Deg C

0.003 nanoseconds

Pulse Rise Time Rating:

6.0 nanoseconds

NSN 5999-01-199-2866

Delay Line - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

16 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100