

View Online at <https://aerobasegroup.com/nsn/5999-01-199-6992>

**Body Style:**

Rectangular, bracketed

**Slot Length:**

0.250 inches

**Overall Length:**

6.000 inches

**Frequency Rating:**

Between 0.000 megahertz and 100.000 megahertz

**Body Length:**

4.800 inches

**Body Width:**

1.690 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

5.400 inches

**Longest Vertical Distance Between Mounting Centers:**

1.000 inches

**Operating Temperature Range:**

-20.0/+70.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4

**Material And Location:**

Aluminum alloy, qq-a-250/11, alloy 6061, t6 case

**Surface Treatment And Location:**

Chromate case

**Input Impedance Rating:**

50.000 ohms

**Output Impedance Rating:**

50.000 ohms

**Body Depth:**

2.000 inches

**Mounting Facility:**

Slot

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

3.000

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

90.000 nanoseconds single section

**Terminal Type And Quantity:**

2 coaxial receptacle

**Err Default:**

Err default and err default

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100