

View Online at <https://aerobasegroup.com/nsn/5999-01-199-6992>

Body Style:

Rectangular, bracketed

Slot Length:

0.250 inches

Overall Length:

6.000 inches

Frequency Rating:

Between 0.000 megahertz and 100.000 megahertz

Body Length:

4.800 inches

Body Width:

1.690 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

5.400 inches

Longest Vertical Distance Between Mounting Centers:

1.000 inches

Operating Temperature Range:

-20.0/+70.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4

Material And Location:

Aluminum alloy, qq-a-250/11, alloy 6061, t6 case

Surface Treatment And Location:

Chromate case

Input Impedance Rating:

50.000 ohms

Output Impedance Rating:

50.000 ohms

Body Depth:

2.000 inches

Mounting Facility:

Slot

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

3.000

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

90.000 nanoseconds single section

Terminal Type And Quantity:

2 coaxial receptacle

Err Default:

Err default and err default

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100