NSN 5999-01-213-8656



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-213-8656 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.700 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Voltage Rating:** Not rated Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.320 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 300.000 nanoseconds single section **Delay Time Variation Per Deg Celsius:**

Delay Time Variation Per De 0.030 nanoseconds Pulse Rise Time Rating:

4.0 nanoseconds

NSN 5999-01-213-8656

Delay Line - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100