## NSN 5999-01-214-0904



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-214-0904 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Voltage Rating:** Not rated Input Impedance Rating: 300.000 ohms **Output Impedance Rating:** 300.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.260 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 

Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 300.000 nanoseconds single section **Delay Time Variation Per Deg Celsius:** Not rated **Pulse Rise Time Rating:** Not rated

## NSN 5999-01-214-0904

Delay Line - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

14 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100