## NSN 5999-01-217-1747

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-217-1747 **Body Style:** Rectangular **Body Length:** 0.800 inches **Body Width:** 0.425 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 14 **Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Metal case and ceramic body **Body Depth:** 0.270 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular Signal Delay Method: Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 92.000 nanoseconds single section **Pulse Rise Time Rating:** 4.0 nanoseconds **Terminal Type And Quantity:** 14 pin Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5999-01-217-1747

Delay Line - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32100