

View Online at <https://aerobasegroup.com/nsn/5999-01-217-3901>

**Body Style:**

Rectangular

**Body Length:**

0.500 inches

**Body Width:**

0.400 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.300 inches

**Longest Vertical Distance Between Mounting Centers:**

0.300 inches

**Operating Temperature Range:**

+0.0 to 70.0 degrees celsius

**Mounting Facility Quantity:**

8

**Voltage Rating:**

Between 4.750 volts and 5.250 volts

**Material And Location:**

Plastic, diallyl phthalate, mil-m-14, type sdc body

**Surface Treatment And Location:**

Plastic, epoxy body

**Body Depth:**

0.250 inches

**Mounting Facility:**

Pin

**Mounting Provision Arrangement Style:**

Four position rectangular

**Signal Delay Method:**

Solid state

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

500.000 nanoseconds single section

**Segment Quantity Per Section:**

5 single section

**Segment Delay Time:**

100.000 nanoseconds single section all segments

**Pulse Rise Time Rating:**

4.0 nanoseconds

**Terminal Type And Quantity:**

8 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100