## NSN 5999-01-217-4191



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-217-4191 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.725 inches **Body Width:** 0.290 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.620 inches **Longest Vertical Distance Between Mounting Centers:** 0.325 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Mounting Facility Quantity:** 14 **Voltage Rating:** 25.000 volts Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.225 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 0.500 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 

40.000 nanoseconds single section **Segment Quantity Per Section:** 10 single section

## NSN 5999-01-217-4191

Delay Line - Page 2 of 2



4.000 nanoseconds single section all segments

**Delay Time Variation Per Deg Celsius:** 

Not rated

**Pulse Rise Time Rating:** 

6.0 nanoseconds

**Terminal Type And Quantity:** 

14 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100