NSN 5999-01-219-9850



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-219-9850 **Body Style:** Cylindrical **Body Diameter:** 1.600 inches **Body Length:** 0.438 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.200 inches **Shortest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.600 inches **Operating Tempurature Range:** -55.0 to 105.0 degrees celsius **Mounting Facility Quantity:** 3 **Material And Location:** Plastic, epoxy case Input Impedance Rating: 325.000 ohms **Output Impedance Rating:** 325.000 ohms Frequency Bandwidth: 16000.7 kilohertz **Mounting Facility:** Terminal **Mounting Provision Arrangement Style:** Isosceles triangle **Attenuation In Decibels:** 20.000 **Signal Delay Method:** Inductance **Delay Time Variation Method:** Variable **Section Delay Time:** 300.000 nanoseconds single section

Pulse Rise Time Rating: 21.0 nanoseconds

Terminal Type And Quantity:

3 pin

NSN 5999-01-219-9850

Delay Line - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100