## NSN 5999-01-220-6306

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-220-6306

**Body Style:** Rectangular **Body Length:** 0.780 inches **Body Width:** 0.300 inches **Individual Section Quantity:** 1 Longest Horizontal Distance Between Mounting Centers: 0.600 inches Longest Vertical Distance Between Mounting Centers: Between 0.310 inches and 0.350 inches **Mounting Facility Quantity:** 14 Voltage Rating: 25.000 volts Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms **Body Depth:** 0.225 inches **Mounting Facility:** 

Pin

**Mounting Provision Arrangement Style:** 

Four position rectangular

#### Signal Delay Method:

Lumped constant

**Delay Time Variation Method:** 

Tapped

#### **Section Delay Time:**

50.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

5.000 nanoseconds single section all segments

**Pulse Rise Time Rating:** 

8.0 nanoseconds

**Terminal Type And Quantity:** 

14 pin

Shelf Life:

N/a

# NSN 5999-01-220-6306

Delay Line - Page 2 of 2

Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

Fiig:

A32100

