

View Online at <https://aerobasegroup.com/nsn/5999-01-221-0687>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.146 inches and 0.166 inches

Overall Length:

Between 0.985 inches and 1.015 inches

Temperature Rating:

-65.0 degrees fahrenheit and 387.0 degrees fahrenheit

Overall Width:

Between 0.985 inches and 1.015 inches

Aperture Diameter:

Between 0.625 inches and 0.645 inches

Outside Corner Radius:

Between 0.131 inches and 0.151 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.709 inches and 0.729 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.709 inches and 0.729 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.138 inches and 0.143 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.138 inches and 0.143 inches

Cross-sectional Height:

Between 0.022 inches and 0.042 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Rubber fluorosilicone class fq environmental seal

Material Specification:

Mil-r-25988, type 2, class 1, grade 70 military specification single material response environmental seal

Precious Material And Location:

Throughout rf shielding gasket silver

Precious Material:

Silver

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0

Mil-std (military Standard):

Mil-r-25988 spec.