## NSN 5999-01-221-0687

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-221-0687
Cross Sectional Shape:
Emi
Hole Diameter:
Between 0.146 inches and 0.166 inches
Overall Length:
Between 0.985 inches and 1.015 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 387.0 degrees fahrenheit
Overall Width:
Between 0.985 inches and 1.015 inches
Aperture Diameter:
Between 0.625 inches and 0.645 inches
Outside Corner Radius:
Between 0.131 inches and 0.151 inches
Center To Center Distance Between Bolt Holes Along Width:
Between 0.709 inches and 0.729 inches
Center To Center Distance Between Bolt Holes Along Length:
Between 0.709 inches and 0.729 inches
Outside Edge To Bolt Hole Center Distance Along Width:
Between 0.138 inches and 0.143 inches
Outside Edge To Bolt Hole Center Distance Along Length:
Between 0.138 inches and 0.143 inches
Cross-sectional Height:
Between 0.022 inches and 0.042 inches
Bolt Hole Quantity:
4
Environmental Protection Material Location:
Throughout rf shielding gasket
Material:
Rubber fluorosilicone class fq environmental seal
Material Specification:
Mil-r-25988, type 2, class 1, grade 70 military specification single material response environmental seal
Precious Material And Location:
Throughout rf shielding gasket silver
Precious Material:
Silver
Style Designator:
Non-circular and the second se
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5999-01-221-0687

Electronic Shielding Gasket - Page 2 of 2



Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-25988 spec.