NSN 5999-01-222-2292

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-222-2292

Body Style:
Rectangular
Body Length:
0.785 inches
Body Width:
Between 0.285 inches and 0.315 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
14
Voltage Rating:
50.000 volts
Material And Location:
Plastic, epoxy case and copper terminal
Surface Treatment And Location:
Tin plate terminal
Input Impedance Rating:
220.000 ohms
Output Impedance Rating:
220.000 ohms
Body Depth:
Between 0.280 inches and 0.320 inches
Unpackaged Unit Weight:
2.5 grams
Mounting Facility:
Terminal
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
142.500 nanoseconds single section and 157.500 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
14.250 nanoseconds single section all segments and 15.750 nanoseconds single section all segments
Pulse Rise Time Rating:

12.0 nanoseconds

NSN 5999-01-222-2292

Delay Line - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

14 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100