NSN 5999-01-222-3232

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-222-3232 **Body Style:** Rectangular **Body Length:** 1.300 inches **Body Width:** Between 0.285 inches and 0.315 inches **Individual Section Quantity:** 1 **Longest Horizontal Distance Between Mounting Centers:** Between 0.580 inches and 0.620 inches **Longest Vertical Distance Between Mounting Centers:** Between 0.570 inches and 0.590 inches **Mounting Facility Quantity:** 24 **Material And Location:** Fiberglass, epoxy case **Surface Treatment And Location:** Tin plated case Input Impedance Rating: 220.000 ohms **Output Impedance Rating:** 220.000 ohms **Body Depth:** Between 0.580 inches and 0.620 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular Signal Delay Method: Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 14.250 nanoseconds single section **Terminal Type And Quantity:** 24 pin Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 5999-01-222-3232Delay Line - Page 2 of 2



Fiig:

A32100