## NSN 5999-01-231-2538

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-231-2538 **Body Style:** Rectangular **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 13 **Voltage Rating:** 7.000 volts **Material And Location:** Plastic, mil-m-14, type sdg-f body **Body Depth:** 0.260 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular Signal Delay Method: Solid state **Delay Time Variation Method: Tapped Section Delay Time:** 125.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

12.500 nanoseconds single section all segments

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

13 pin

## NSN 5999-01-231-2538

Delay Line - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100