## NSN 5999-01-231-9541

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-231-9541 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.900 inches **Body Width:** 0.280 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 10 **Voltage Rating:** 50.000 volts **Material And Location:** Iron alloy terminal **Surface Treatment And Location:** Tin plate terminal Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth:

Not rated

Body Depth:

0.250 inches

Mounting Facility:
Terminal

Attenuation In Decibels:
1.000

Signal Delay Method:
Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:
50.000 microseconds single section

Segment Quantity Per Section:

10 single section

## NSN 5999-01-231-9541

Delay Line - Page 2 of 2



## **Segment Delay Time:**

5.000 microseconds single section all segments

**Delay Time Variation Per Deg Celsius:** 

Not rated

**Pulse Rise Time Rating:** 

10.0 nanoseconds

**Terminal Type And Quantity:** 

10 tab solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A32100