

NSN 5999-01-237-1536 Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-237-1536 **Body Style:** Rectangular **Adjustment Device Quantity: Adjustment Device Drive Type:** Slotted screw **Body Length:** 2.250 inches **Body Width:** 0.750 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.800 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

Inclosure Type:

Encased

4

Mounting Facility Quantity:

Material And Location:

Plastic, epoxy resin case

Input Impedance Rating:

1.000 kilohms

Body Depth:

0.350 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

0.500

Signal Delay Method:

Inductance

Delay Time Variation Method:

Variable

Section Delay Time:

85.000 nanoseconds single section

Terminal Type And Quantity:

4 pin

NSN 5999-01-237-1536

Delay Line - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100