NSN 5999-01-237-7376

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-237-7376

Body Style:
Rectangular
Body Length:
0.300 inches
Body Width:
Between 0.740 inches and 0.780 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
0.600 inches
Longest Vertical Distance Between Mounting Centers:
Between 0.310 inches and 0.350 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Mounting Facility Quantity:
14
Material And Location:
Plastic, epoxy case
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Body Depth:
0.187 inches
Mounting Facility:
Terminal
Mounting Provision Arrangement Style:
Four position rectangular
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
200.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
20.000 nanoseconds single section all segments
Pulse Rise Time Rating:
40.0 nanoseconds
Terminal Type And Quantity:
14 pin

NSN 5999-01-237-7376

Delay Line - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100