

View Online at <https://aerobasegroup.com/nsn/5999-01-238-7527>

Body Style:

Rectangular

Body Length:

1.650 inches

Body Width:

0.350 inches

Individual Section Quantity:

2

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

17

Voltage Rating:

7.000 volts

Input Impedance Rating:

390.000 ohms

Output Impedance Rating:

390.000 ohms

Body Depth:

0.400 inches

Step Quantity:

64

Mounting Facility:

Terminal

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Programmable

Delay Time Per Step:

Between 0.475 nanoseconds and 1.575 nanoseconds

Section Delay Time:

18.000 nanoseconds all sections and 20.000 nanoseconds all sections

Segment Quantity Per Section:

32 all sections

Segment Delay Time:

0.475 nanoseconds all sections all segments and 1.575 nanoseconds all sections all segments

Pulse Rise Time Rating:

25.0 nanoseconds

Terminal Type And Quantity:

17 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100