Electronic Shielding Gasket - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5999-01-242-5049



| Cross Sectional Shape: |
|---|
| Emi |
| Hole Diameter: |
| 0.150 inches |
| Overall Length: |
| Between 0.923 inches and 0.953 inches |
| Tempurature Rating: |
| -55.0 degrees celsius and 200.0 degrees celsius |
| Overall Width: |
| Between 0.923 inches and 0.953 inches |
| Aperture Diameter: |
| Between 0.610 inches and 0.640 inches |
| Outside Corner Radius: |
| 0.109 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| Between 0.704 inches and 0.734 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| Between 0.704 inches and 0.734 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.0095 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.0095 inches |
| Cross-sectional Height: |
| Between 0.020 inches and 0.035 inches |
| Bolt Hole Quantity: |
| 4 |
| Environmental Protection Material Location: |
| Throughout rf shielding gasket |
| Material: |
| Rubber silicone class q environmental seal |
| Material Specification: |
| Zz-r-765, class 3, grade 30 federal specification single material response environmental seal |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |