1-244-0617



obasegroup.com/nsn/5999-01-244-0617

NSN 5999-01-244
Delay Line - Page 1 of 2
View Online at https://aerobasegrou
Body Style:
Rectangular
Frequency Rating:
17.000 kilohertz
Body Length:
6.030 inches
Body Width:
2.030 inches
Individual Section Quantity:
1
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Mounting Facility Quantity:
13
Material And Location:
Metal case
Surface Treatment And Location:
Painted case
Input Impedance Rating:
200.000 ohms
Output Impedance Rating:
200.000 ohms
Body Depth:
0.078 inches

Mounting Facility:

Pin

Attenuation In Decibels:

0.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time: 500.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

50.000 nanoseconds single section all segments

Pulse Rise Time Rating:

20.000 nanoseconds

Terminal Type And Quantity:

13 pin

NSN 5999-01-244-0617

Delay Line - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100

