## NSN 5999-01-245-9733



Electrical Contact - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-245-9733 **Overall Length:** 0.203 inches **Overall Diameter:** 0.072 inches **Cable Entrance Diameter:** 0.054 inches Pin Accommodation Length: Between 0.100 inches and 0.170 inches **Pin Accommodation Diameter:** Between 0.016 inches and 0.021 inches **Mounting Method:** Force fit Material: Copper alloy body and contact **Material Specification:** Qq-c-530 federal specification single material response body and contact or qq-c-533 federal specification single material response body and contact **Precious Material And Location:** Body and contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Surface Treatment:** Gold body and contact **Surface Treatment Specification:** Mil-g-45204 military specification single treatment response body and contact **Style Designator:** Cylindrical shape **Test Data Document:** 81349-mil-s-83505 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 1 crimp end opposite contact **Specification Data:** 81349-mil-s-83505/5 government specification Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

Demilitarization:

## NSN 5999-01-245-9733

Electrical Contact - Page 2 of 2



Mil-std (military Standard):

Mil-g-45204 spec.