

View Online at <https://aerobasegroup.com/nsn/5999-01-246-3311>

Body Style:

Rectangular

Body Length:

0.900 inches

Body Width:

0.280 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

16

Voltage Rating:

50.000 volts

Material And Location:

Nickel, qq-n-281, class a terminal

Surface Treatment And Location:

Tin plate terminal

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Body Depth:

0.280 inches

Mounting Facility:

Terminal

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

100.000 nanoseconds single section

Pulse Rise Time Rating:

20.0 nanoseconds

Terminal Type And Quantity:

16 tab solder lug

Test Data Document:

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100