NSN 5999-01-246-3311

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-246-3311

Body Style: Rectangular **Body Length:** 0.900 inches **Body Width:** 0.280 inches **Individual Section Quantity:** 1 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 16 Voltage Rating: 50.000 volts Material And Location: Nickel, qq-n-281, class a terminal **Surface Treatment And Location:** Tin plate terminal Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms **Body Depth:** 0.280 inches **Mounting Facility:** Terminal Signal Delay Method: Lumped constant **Delay Time Variation Method:** Tapped Section Delay Time: 100.000 nanoseconds single section **Pulse Rise Time Rating:** 20.0 nanoseconds **Terminal Type And Quantity:** 16 tab solder lug **Test Data Document:**

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:

```
N/a
```

NSN 5999-01-246-3311

Delay Line - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A32100

