NSN 5999-01-246-3312



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-246-3312 **Body Style:** Rectangular **Body Length:** 0.900 inches **Body Width:** 0.280 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 16 **Voltage Rating:** 50.000 volts **Material And Location:** Plastic body and iron alloy terminal **Surface Treatment And Location:** Tin plate terminal Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms **Body Depth:** 0.280 inches **Mounting Facility:** Terminal Signal Delay Method: Solid state **Delay Time Variation Method: Tapped Section Delay Time:** 200.000 nanoseconds single section **Pulse Rise Time Rating:** 40.0 nanoseconds **Terminal Type And Quantity:** 16 tab solder lug

Test Data Document:

rest Data Document:

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

NSN 5999-01-246-3312

Delay Line - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100