

View Online at <https://aerobasegroup.com/nsn/5999-01-247-1192>

**Cross Sectional Shape:**

Mesh and metal

**Hole Diameter:**

Between 0.195 inches and 0.205 inches

**Overall Length:**

Between 18.250 inches and 18.310 inches

**Temperature Rating:**

-45.6 degrees celsius and 71.0 degrees celsius

**Overall Width:**

Between 10.930 inches and 10.970 inches

**Inside Corner Radius:**

0.060 inches

**Aperture Width:**

9.826 inches

**Aperture Length:**

17.156 inches

**Center To Center Distance Between Bolt Holes Along Width:**

4.000 inches

**Center To Center Distance Between Bolt Holes Along Length:**

4.000 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 1.125 inches and 1.155 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 3.460 inches and 3.490 inches

**Cross Section Outside Diameter:**

Between 0.125 inches and 0.249 inches

**Cross-sectional Height:**

0.125 inches

**Minor Height:**

0.125 inches

**Bolt Hole Quantity:**

14

**Environmental Protection Material Location:**

Throughout rf shielding gasket

**Special Features:**

Aluminum alloy frame 6063-t42, qq-a-200/9 with a chemical film finish per mil-c-5541, class 1a or class 3; four 0.380 in. Diameter indentations on 3.500 in. X 18.250 in. Min to 18.310 in. Maximum c to c

**Material:**

Steel emi/rfi conductor

**Material Specification:**

Astm b-250, class t40a federal specification single material response emi/rfi conductor

**Surface Treatment:**

Tin emi/rfi conductor and copper emi/rfi conductor

**Surface Treatment Specification:**

Astm b-250, class t40a federal specification all treatment responses emi/rfi conductor

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0