NSN 5999-01-248-0050

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-248-0050

| Identification Code Color: | | | | | | |
|--|--|--|--|--|--|--|
| Yellow | | | | | | |
| Overall Length: | | | | | | |
| 0.987 inches | | | | | | |
| Overall Diameter: | | | | | | |
| Between 0.156 inches and 0.164 inches | | | | | | |
| Cable Entrance Diameter: | | | | | | |
| Between 0.064 inches and 0.080 inches | | | | | | |
| Pin Accommodation Length: | | | | | | |
| 0.515 inches | | | | | | |
| Pin Accommodation Diameter: | | | | | | |
| Between 0.098 inches and 0.102 inches | | | | | | |
| Current Rating In Amps: | | | | | | |
| 25.0 | | | | | | |
| Mounting Method: | | | | | | |
| Force fit | | | | | | |
| Crimping Tool Identifying Number: | | | | | | |
| M22520/1-01 | | | | | | |
| Material: | | | | | | |
| Steel body | | | | | | |
| Material Specification: | | | | | | |
| Qq-c-533 federal specification single material response contact | | | | | | |
| Precious Material And Location: | | | | | | |
| Contact surfaces gold | | | | | | |
| Precious Material And Weight: | | | | | | |
| 0.005 gold grains, troy | | | | | | |
| Precious Material: | | | | | | |
| Gold | | | | | | |
| Surface Treatment: | | | | | | |
| Passivate body | | | | | | |
| Surface Treatment Specification: | | | | | | |
| Mil-g-45204 military specification single treatment response contact | | | | | | |
| Style Designator: | | | | | | |
| Socket contact | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 1 crimp and solder axially at one end | | | | | | |
| Specification Data: | | | | | | |
| 33875-cn-b0049 manufacturers specification control | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |
| Unit Of Measure: | | | | | | |

--

NSN 5999-01-248-0050

Electrical Contact - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-g-45204 spec.