## NSN 5999-01-249-8310

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-249-8310 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity: Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Brass terminal err-100 err-100 **Surface Treatment And Location:** Plastic, epoxy body err-100 err-100 Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.320 inches **Mounting Facility:** Pin **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 250.000 nanoseconds single section

Output Impedance Rating:
Not rated
Frequency Bandwidth:
Not rated
Body Depth:
0.320 inches
Mounting Facility:
Pin
Attenuation In Decibels:
Not rated
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
250.000 nanoseconds single section
Segment Quantity Per Section:
5 single section

## NSN 5999-01-249-8310

Delay Line - Page 2 of 2



Segment Delay Time:
50.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
5.0 nanoseconds
Terminal Type And Quantity:
8 pin
Special Features:
Four mtg feet
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

**Fiig:** A32100