NSN 5999-01-250-1502

Electronic Shielding Gasket - Page 1 of 1



/iew Online at https://aerobasegroup.com/nsn/5999-01-250-1502

| view Online at https://aerobasegroup.com/nsn/5999-01-250-1502 |
|--|
| Cross Sectional Shape: |
| Emi |
| Hole Diameter: |
| Between 0.110 inches and 0.130 inches |
| Overall Length: |
| Between 1.383 inches and 1.399 inches |
| Overall Width: |
| Between 1.383 inches and 1.399 inches |
| Aperture Diameter: |
| Between 1.125 inches and 1.141 inches |
| Outside Corner Radius: |
| Between 0.146 inches and 0.166 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| Between 1.005 inches and 1.025 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| Between 1.005 inches and 1.025 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.193 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.193 inches |
| Cross-sectional Height: |
| Between 0.026 inches and 0.036 inches |
| Bolt Hole Quantity: |
| 4 |
| Material: |
| Rubber silicone class q environmental seal |
| Material Specification: |
| Zz-r-765 class 3, grade 30 federal specification single material response environmental seal |
| Style Designator: |
| Non-circular |
| Test Data Document: |
| 81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-c-28840/24 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Fiig: A032a0

No

Demilitarization: