

View Online at <https://aerobasegroup.com/nsn/5999-01-251-2560>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.1141/+0.1169 inches

**Body Style:**

Rectangular

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

7.625 inches

**Body Width:**

1.250 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.400 inches

**Longest Vertical Distance Between Mounting Centers:**

0.250 inches

**Operating Temperature Range:**

+0.0/+65.0 degrees celsius

**Stud Length:**

Between 0.410 inches and 0.530 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2

**Material And Location:**

Metal case

**Surface Treatment And Location:**

Paint case

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Body Depth:**

0.780 inches

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position diagonal

**Attenuation In Decibels:**

1.500

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

990.000 nanoseconds single section

**Pulse Rise Time Rating:**

100.0 nanoseconds

**Terminal Type And Quantity:**

2 wire loop

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100