

View Online at <https://aerobasegroup.com/nsn/5999-01-251-2560>

Thread Class:

2a

Thread Pitch Diameters:

+0.1141/+0.1169 inches

Body Style:

Rectangular

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

7.625 inches

Body Width:

1.250 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.400 inches

Longest Vertical Distance Between Mounting Centers:

0.250 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Stud Length:

Between 0.410 inches and 0.530 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Material And Location:

Metal case

Surface Treatment And Location:

Paint case

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

0.780 inches

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position diagonal

Attenuation In Decibels:

1.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

990.000 nanoseconds single section

Pulse Rise Time Rating:

100.0 nanoseconds

Terminal Type And Quantity:

2 wire loop

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100