

View Online at <https://aerobasegroup.com/nsn/5999-01-252-8812>

**Body Style:**

Rectangular

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

1.310 inches

**Body Width:**

0.500 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.000 inches

**Longest Vertical Distance Between Mounting Centers:**

0.300 inches

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

4

**Voltage Rating:**

50.000 volts

**Material And Location:**

Fiberglass, epoxy case

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Body Depth:**

0.312 inches

**Mounting Facility:**

Pin

**Mounting Provision Arrangement Style:**

Four position rectangular

**Signal Delay Method:**

Inductance

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

30.000 nanoseconds single section

**Pulse Rise Time Rating:**

6.0 nanoseconds

**Terminal Type And Quantity:**

4 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100