## NSN 5999-01-253-1534

A222a0

Mil-std (military Standard):

Mil-g-45204 spec.



Electrical Contact - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5999-01-253-1534 **Overall Length:** 1.156 inches **Overall Diameter:** Between 0.276 inches and 0.284 inches **Mounting Method:** Force fit **Crimping Tool Identifying Number:** M22520/5-01 **Special Features:** 50.000 ohm impedance; for use with m17/113-rg316, m17/119-rg174, and m17/94-rg179 type cable Material: Plastic polytetrafluoroethylene contact insulation **Material Specification:** Ams 3651 federal specification single material response contact insulation or ams 3659 federal specification single material response contact **Precious Material And Location:** Body and contact surface gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Surface Treatment:** Gold body and contact and copper body and contact **Surface Treatment Specification:** Mil-g-45204, type i or ii, class 2, grade c military specification 1st treatment response body and contact and mil-c-14550 military specification 2nd treatment response body and contact **Style Designator:** Pin center contact **Terminal Type And Quantity:** 1 crimp end opposite contact Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: