## NSN 5999-01-254-2222



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-254-2222 **Body Style:** Rectangular, front connection **Overall Depth:** Any acceptable Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.450 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.400 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 14 **Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Plastic, epoxy case Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.300 inches **Mounting Facility:** Terminal **Mounting Provision Arrangement Style:** 

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Solid state

## NSN 5999-01-254-2222

Delay Line - Page 2 of 2



Delay Time Variation Method:
Tapped
Section Delay Time:
45.000 nanoseconds single section
Segment Quantity Per Section:
9 single section
Segment Delay Time:
5.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
4.0 nanoseconds
Terminal Type And Quantity:
14 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32100