NSN 5999-01-258-2131

No

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-258-2131

| Cross Sectional Shape: |
|--|
| Mesh and metal |
| Hole Diameter: |
| 0.375 inches |
| Overall Length: |
| 26.380 inches |
| Overall Width: |
| 15.520 inches |
| Aperture Width: |
| 14.144 inches |
| Aperture Length: |
| 25.004 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 8.875 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.438 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.438 inches |
| Cross Section Outside Diameter: |
| Between 0.157 inches and 0.219 inches |
| Cross-sectional Height: |
| 0.125 inches |
| Minor Height: |
| 0.125 inches |
| Bolt Hole Quantity: |
| 11 |
| Special Features: |
| Twenty-five 0.062 in. Diameter pilot holes spaced irregularly around frame; three mtg holes on one side of length are equally spaced 8.625 |
| in. C to c, four mtg holes on other side of length are irregularly spaced |
| Material: |
| Nickel alloy emi/rfi conductor and aluminum alloy 6063 emi/rfi conductor |
| Material Specification: |
| Qq-n-281, class a, form 7 federal specification 1st material response emi/rfi conductor and qq-a-200/9, aluminum alloy 6063, temper 4 |
| federal specification 2nd material response emi/rfi conductor |
| Surface Treatment: |
| Chromate emi/rfi conductor |
| Surface Treatment Specification: |
| Mil-c-5541, class 3 military specification single treatment response emi/rfi conductor |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5999-01-258-2131

Electronic Shielding Gasket - Page 2 of 2



Fiig:

A032a0

Mil-std (military Standard):

Mil-c-5541 spec.