## NSN 5999-01-259-5609

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-259-5609 **Body Style:** Rectangular **Body Length:** 0.785 inches **Body Width:** 0.320 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -25.0/+125.0 degrees celsius **Inclosure Type: Encased Mounting Facility Quantity: Surface Treatment And Location:** Tin plated terminal Input Impedance Rating: 200.000 ohms **Output Impedance Rating:** 200.000 ohms **Body Depth:** 0.285 inches **Mounting Facility:** Pin **Attenuation In Decibels:** 1.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 100.000 nanoseconds single section **Segment Quantity Per Section:** 10 single section **Segment Delay Time:** 10.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 16.0 nanoseconds **Terminal Type And Quantity:** 

14 pin

## NSN 5999-01-259-5609

Delay Line - Page 2 of 2



Speci	ial F	eat	ures	,

Two rows, seven terminals per row mtd 0.100 in. Centers

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100