NSN 5999-01-260-2927

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-260-2927

| Overall Length: |
|--|
| 1.089 inches |
| Overall Height: |
| 0.025 inches |
| Overall Width: |
| 0.030 inches |
| Voltage Rating In Volts: |
| 300.0 ac |
| Pin Accommodation Length: |
| 0.169 inches |
| Pin Length: |
| 0.750 inches |
| Mating Contact Width: |
| 0.021 inches |
| Pin Width: |
| 0.025 inches |
| Current Rating In Amps: |
| 3.0 |
| Mounting Method: |
| Force fit |
| Material: |
| Copper alloy body and contact |
| Material Specification: |
| Qq-c-533 federal specification single material response body and contact |
| Precious Material And Location: |
| Body and contact surfaces gold |
| Precious Material And Weight: |
| 0.005 gold grains, troy |
| Precious Material: |
| Gold |
| Surface Treatment: |
| Gold body and contact |
| Surface Treatment Specification: |
| Mil-g-45204, type ii, grade c, class 1 military specification single treatment response body and contact |
| Style Designator: |
| Post contact |
| Test Data Document: |
| 81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 1 pin end opposite contact |

81349-mil-c-28754/36 government specification

Specification Data:

NSN 5999-01-260-2927

Electrical Contact - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

Shelf Life:

Mil-std (military Standard):

Mil-g-45204 spec.